



www.redring.co.uk

Selectronic Thermostatic Shower & Level Access Pump Pack



The 'One Box' Thermostatic Shower & Level Access Pump

- The market leading Selectronic is the only shower to meet the requirements of the Disability Discrimination Act (DDA)
- Total push button operation, with tactile coding and audible feedback
- The only shower to achieve 'Inclusive Design' status, endorsed by the RNIB
- Additional time delay adjustment for start-up and over run
- Perfect for modern wetrooms

Combined in perfect harmony with the level access pump. Using a diaphragm (not impeller) pump action, it removes residual shower waste including hair, grit and gel - reducing blockages!

Approvals *



* Please note that the pump has only IPX4 and CE approvals. The Selectronic Shower has all the approvals indicated.

How it works

The Redring Selectronic electric shower controls the Level Access Pump directly, thereby removing the need to fit a flow switch or any associated wiring. The shower is available in two ratings; 8.5kW and 9.5kW.

Product Codes

Redring Selectronic Level Access Pump Packs	
53557090	8.5kW 240V
53558090	9.5kW 240V

Selectronic Level Access Pump Pack Benefits:

- The only shower to meet the requirements of the Disability Discrimination Act (DDA)
- The first shower to achieve the BEAB Care Mark
- The only shower to achieve 'Inclusive Design' status, endorsed by the RNIB
- Temperature can be capped at 40°C with cooler adjustment and no accidental increase of temperature when lock mode is selected
- Total push button operation with tactile coding and audible feedback
- The Selectronic shower has a 3 year (UK) parts and labour manufacturer guarantee
- The pump has a 2 year (UK) parts and labour manufacturer guarantee
- Additional time delay adjustment for start-up and over run

Where a gravity drain is not an option, Selectronic pump kits provide a reliable solution for draining showers.

- Diaphragm (not impeller) pump action which removes residual shower waste including hair, grit and gel - without blocking
- No regular maintenance required
- Designed for level access showering such as wetrooms or care applications
- Low voltage pump for safe operation
- Meets all European standards

The Selectronic shower variant for use with the Selectronic pump system is fully, third party, approved by BEAB to EN 60 335-1: 1995 (Safety of household and similar electrical appliances) and EN 60 335-2-35 (The particular requirements for instantaneous water heaters).

applied energy


Morley Way
Peterborough
UK
PE2 9JJ

t: +44 (0) 1733 456789
f: +44 (0) 1733 310606
w: www.applied-energy.com
w: www.redring.co.uk


Thermostatic Shower & Level Access Pump all in one box




Selectronic Thermostatic Shower including 2m hose and 1m riser rail




Pump Shroud




Shower Drain Pump




Pump Wall Plate




Shower Trap




Shower Drain Pump Control Unit




Shroud Cover Screw x2




15 mm Speedfit Connector x2



22 mm Speedfit Connector x2



32 mm Reducer



19 mm Reducer